

D210 Mobile Payment Terminal

- Contactless, Chip, Magstripe
- 3G, Bluetooth, WiFi
- iOS® & Android™ Compatible
- Visa & MasterCard® NFC
- PCI PTS 4.x Certified
- Apple® MFi Approved

PAX's D210 is a compact mobile payment device designed to interact with customers. Supporting Bluetooth, WiFi, 3G (WCDMA) or cable connection, the D210 connects to a wide range of existing and new smart devices to keep up with an emerging marketplace. Apple Inc. has given the D210 a special certification called MFi meaning that Apple has tested and approved the D210 to meet the highest performance standards for integration with any iPad or iPhone.

Your Payment Partner of Choice



D210 Mobile Payment Terminal

Features & Benefits





High Reliability & Exceptional Performance

- Smart card, magstripe & contactless enabled
- Stylishly designed for comfort and convenience
- Contactless card reader supporting NFC 2.8 inch color screen
- Large memory capacity

Unprecedented Security

- PCI PTS 4.x approved
- Secure key embedded area

Perfect Expansibility

- Open and flexible OS for customized value-added services
- Supports WiFi, Bluetooth and 3G (WCDMA)

Specifications

Processor

32-bit ARM 11

Memory

192MB (128MB Flash, 64MB SDRAM) Micro SD (TF card) up to 32GB

Display

2.8 inch TFT color LCD, 320 x 240 pixels e-signature (optional)

Printer

High-speed thermal printer, speed: 30 lps Paper roll width / diameter: 58mm / 40mm

Keypad

10 numeric & 8 function keys

Magnetic card reader

Track1 / 2 / 3, Bi-directional

Smart Card Reader

EMVL1 & L2 certified

Contactless Card Reader

MasterCard Contactless & Visa payWave AMEX Expresspay Discover D-PAS ISO14443 Type A/B Mifare, Felica, NFC

Communication

Bluetooth 4.0 / WiFi 3G (WCDMA) (optional)

Card slots

2 SAMs, 1 SIM or 1 SAM, Dual SIM

Peripheral Ports

1 x Mini USB (OTG), 1 x Mini USB (RS232) 1 x Power port

Security

PCI PTS 4.x certified

Environmental

0°C to 50°C (32°F to 122°F) operating temperature -20°C to 70°C (-4°F to 158°F) storage temperature 10% to 93% relative humidity, non-condensing

Voltage

Input: 100 - 240V AC, 50 / 60 Hz, 0.3A Output: 9VDC, 1A

Battery

Li-ion battery, 7.4V, 2300mAH

Physical

Length: 162.5mm Width: 80mm Height: 56mm

Weight

360g with battery

Accessories

Adapter Charging Base (optional)

Certifications

PCI PTS 4.x, SRED EMV Contact L1 & L2 EMV Contactless L1 Visa payWave MasterCard Contactless AMEX Expresspay Discover D-PAS MasterCard TQM



